



acmaudio

CX Series Coaxial Speakers



CX Series Coaxial Speakers



Looking for a stage monitor engineered to satisfy professional demands for pubs, coffee shops, KTV, commercial environments and stages? Want a versatile enclosure suitable for use as a side-fill, front-fill? Then welcome to ACM audio CX low-profile monitor housing. With ACM technology on board, these enclosures project extraordinarily rich, transparent sound, even at very high levels.

And their remarkably linear frequency response enables high volumes with reduced feedback sensitivity. It has been optimised for use as a stage monitor, its multi-functional housing shape and the integrated pole-mount cup allow it to be used for additional applications.

Technical Specification:

	CX-8	CX-10	CX-12	CX-15
<i>Freq. Range (-10dB):</i>	80Hz – 20kHz	70Hz – 20kHz	60Hz – 20kHz	50Hz – 20kHz
<i>Axial Sensitivity (1m/1W):</i>	94dB	96dB	97dB	98dB
<i>Max Calculated SPL (1m):</i>	118dB	122dB	124dB	126dB
<i>Rec. Hi pass Frequency:</i>	50Hz	40Hz	30Hz	25Hz
<i>Long Term Load Power:</i>	120W	200W	250W	300W
<i>Short Term Load Power:</i>	240W	400W	500W	600W
<i>Dispersion (HXV):</i>	60° x 60°	80° x 80°	80° x 80°	90° x 90°
<i>LF Transducer:</i>	8"/50mm	10"/65mm	12"/65mm	15"/75mm
<i>HF Transducer:</i>	1"/34mm	1"/34mm	1"/45mm	1"/45mm
<i>Crossover Frequency:</i>	3000Hz	3000Hz	2800Hz	2100Hz
<i>Nominal Impedance</i>	8 ohms.	8 ohms.	8 ohms.	8 ohms.
<i>Connectors:</i>	Speakon NL4 x 2	Speakon NL4 x 2	Speakon NL4 x 2	Speakon NL4 x 2
<i>Dim (W x H x D)</i>	300 x 338 x 240mm	360 x 420 x 290mm	400 x 502 x 345mm	480 x 605 x 400mm
<i>Net Weight:</i>	7Kg	12Kg	17Kg	27Kg
<i>Shipping Weight:</i>	9Kg	14Kg	20Kg	30Kg